



Machines/Accessories

■ Sealing tank

Isolated stainless steel tank with heating elements, boiling-dry protection, thermostat and draw-off tap, wherein the printed aluminium sheets can be sealed.

- Available in different sizes.



■ Sealing covering balls

Isolation balls with a diameter of about 20 mm intended to put on the seal water surface to ensure that the water evaporates less quickly.

- 1000 balls in 1 package.

■ Sealing pH indicator

Strips of litmus paper for measuring the pH value of the seal water..

■ Sealing rack

Rack for storing sheets with a minimum size of 250 x 325 mm and a maximum size of 500 x 650 mm. The rack can be fitted inside the seal tank.

- Maximum 15 sheets in 1 rack.



		inside dimensions	outside dimensions	
		L x B x H	L x B x H	
I	67 L.	450 x 200 x 750 mm	610 x 280 x 800 mm	1 x 3 kW - 240 V
II	112 L.	750 x 200 x 750 mm	910 x 280 x 800 mm	1 x 3 kW - 240 V
IIA	225 L.	750 x 400 x 750 mm	910 x 480 x 800 mm	2 x 3 kW - 240 V
III	198 L.	1100 x 200 x 900 mm	1260 x 280 x 950 mm	1 x 9 kW - 400 V
IIIA	396L.	1100 x 400 x 900 mm	1260 x 480 x 950 mm	2 x 6 kW - 400 V
IIIB	594L.	1100 x 600 x 900 mm	1260 x 680 x 950 mm	2 x 9 kW - 400 V
IV	300L.	1200 x 200 x 1250 mm	1360 x 280 x 1300 mm	1 x 9 kW - 400 V
IVA	600L.	1200 x 400 x 1250 mm	1360 x 480 x 1300 mm	2 x 6 kW - 400 V
IVB	900L.	1200 x 600 x 1250 mm	1360 x 680 x 1300 mm	2 x 9 kW - 400 V
V	1260L.	2250 x 400 x 1400 mm	2410 x 580 x 1450 mm	4 x 6 kW - 400 V